

## T50R7M4



**Article Number:** 111-04877

**Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66, Purple, 1000/pkg**



### Base Data

**Local Order Number** T50R7M4

**Type** T50R

**Color** Purple (PE)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Standard Cable Tie, 8" Long, 50lb Tensile Strength, PA66, Purple, 1000/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 50.0 lbs

**Minimum Tensile Strength (N)** 225.0 N

**Length L (imperial)** 8.0 "

**Length L (metric)** 202.0 mm

**Width W (imperial)** 0.18 "

**Width W (metric)** 4.6 mm

**Bundle Diameter min (imperial)** 0.06 "

**Bundle Diameter min (metric)** 1.5 mm

**Bundle Diameter max (imperial)** 1.97 "

**Bundle Diameter max (metric)** 50.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 1000

**Carton Quantity** 5000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>US MILSPEC</b>	MS3367-1-7
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	MIL 53421 UL ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes