

T50R9PPC2



Article Number: 111-04931

High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg



Base Data

Local Order Number T50R9PPC2

Type T50R

Color Natural (NA)

- Features and Benefits**
- Polypropylene cable ties provide excellent resistance to chemicals and salts.
 - Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton high temperature cable ties are made of specially formulated materials providing various levels of temperature resistance and performance. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 25.0 lbs

Minimum Tensile Strength (N) 111.0 N

Length L (imperial) 8.0 "

Length L (metric) 202.0 mm

Width W (imperial) 0.19 "

Width W (metric) 4.8 mm

Bundle Diameter min (imperial) 0.5 "

Bundle Diameter min (metric) 12.7 mm

Bundle Diameter max (imperial) 1.75 "

Bundle Diameter max (metric) 44.5 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 5000

Material and Specifications

Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL94 HB
Halogenfree	Yes
Operating Temperature	-40 °F to +239 °F (-40 °C to +115 °C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No