# HellermannTyton

#### T50RDH0HSM4



Article Number: 117-05010

Double Head Tie, 8.3" Long, 50lb Tensile Strength, PA66HS, Black, 1000/pkg

RoHS

#### **Base Data**

Local Order Number T50RDH0HSM4

T50RDH Type

Color Black (BK)

Features and Benefits • Heat stabilized cable ties provide excellent resistance to high heat exposures.

• The tie contains a dual locking design to secure two bundles at once.

· Head design can also provide spacing between parallel bundles.

Bent tail allows for quick insertion into head.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head

also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent

and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Double Head Tie, 8.3" Long, 50lb Tensile Strength, PA66HS, Black, 1000/pkg

### **Product Dimensions**

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 8.3 "

Length L (metric) 210.0 mm

Bundle Diameter 2nd Loop max 0.75 "

(imperial)

Width W (imperial)0.19 "

Width W (metric) 4.7 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 2.0 "

Bundle Diameter max (metric) 50.0 mm

Bundle Diameter 1st Loop max 1.7"

(imperial) Bundle Diameter 1st Loop max (metric)44.4 mm

Bundle Diameter 2nd Loop max 19.0 mm

(metric)

#### **Logistics and Packaging**

Quantity per bag

Package Quantity 1000
Carton Quantity 5000

## **Material and Specifications**

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

CSA Certified No

Flammability UL94 V2

Halogenfree Yes

**Operating Temperature** -40 °F to +257 °F (-40 °C to +125 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes