

T50RSF9C2



Article Number: 111-85789

Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"-.28", PA66, Natural, 100/pkg



Base Data

Local Order Number	T50RSF9C2
Type	T50RSF(U)
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Push Mount design creates quick and easy mounting for installers. • Push mount style creates low insertion and high extraction force. • Ties "clicks" into place upon final installation signaling installer insertion is complete.
Product Description	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"-.28", PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225 N
Length L (imperial)	8.3 "
Length L (metric)	210.0 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Height H (imperial)	0.3 "
Height H (metric)	7.5 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	1.7 "
Bundle Diameter max (metric)	44.0 mm
Panel Thickness max. (imperial)	0.14 "
Panel Thickness max. (metric)	3.5 mm
Panel Thickness min. (imperial)	0.04 "
Panel Thickness min. (metric)	1.0 mm
Mounting Hole Diameter D (imperial)	0.25 - 0.28 "
Mounting Hole Diameter D (metric)	6.4 - 7.1 mm
Mounting Hole Diameter D min (imperial)	0.25 "

Mounting Hole Diameter D max 0.28 "
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max (metric) 7.1 mm

Mounting Hole Diameter D min (metric) 6.4 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 5000
Weight (Metric) 1.5 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
CSA Certified No
Flammability UL94 V2
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes