

## T50RSF9M4



**Article Number:** 126-01011

**Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"-.28", PA66, Natural, 1,000/pkg**



### Base Data

<b>Local Order Number</b>	T50RSF9M4
<b>Type</b>	T50RSF(U)
<b>Color</b>	Natural (NA)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Push Mount design creates quick and easy mounting for installers.</li> <li>• Push mount style creates low insertion and high extraction force.</li> <li>• Ties "clicks" into place upon final installation signaling installer insertion is complete.</li> </ul>
<b>Product Description</b>	Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.
<b>Fixation Method (FF)</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure (Yes/No)</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Short Description</b>	Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"-.28", PA66, Natural, 1,000/pkg

### Product Dimensions

<b>Minimum Tensile Strength (imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (N)</b>	225 N
<b>Length L (imperial)</b>	8.3 "
<b>Length L (metric)</b>	210.0 mm
<b>Width W (imperial)</b>	0.19 "
<b>Width W (metric)</b>	4.7 mm
<b>Height H (imperial)</b>	0.3 "
<b>Height H (metric)</b>	7.5 mm
<b>Bundle Diameter min (imperial)</b>	0.06 "
<b>Bundle Diameter min (metric)</b>	1.6 mm
<b>Bundle Diameter max (imperial)</b>	1.7 "
<b>Bundle Diameter max (metric)</b>	44.0 mm
<b>Panel Thickness max. (imperial)</b>	0.14 "
<b>Panel Thickness max. (metric)</b>	3.56 mm
<b>Panel Thickness min. (imperial)</b>	0.04 "
<b>Panel Thickness min. (metric)</b>	1.00 mm
<b>Mounting Hole Diameter D (imperial)</b>	0.25 - 0.28 "
<b>Mounting Hole Diameter D (metric)</b>	6.4 - 7.1 mm
<b>Mounting Hole Diameter D min (imperial)</b>	0.25 "

Mounting Hole Diameter D max 0.28 "  
(imperial)

Thickness T (imperial) 0.05 "

Mounting Hole Diameter D max 7.1 mm  
(metric)

Mounting Hole Diameter D min (metric) 6.4 mm

Thickness T (Metric) 1.2 mm

## Logistics and Packaging

---

Quantity per bag

Package Quantity 1000

Carton Quantity 5000

## Material and Specifications

---

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes