



T50RTM25E8HM4



Article Number: 126-03504

Fir Tree Push Mount Ties, 8.3" Long, .25" - .28" Mounting Hole, PA66HIRHS, Grey, 1,000/pkg

 RoHS

Base Data

Local Order Number	T50RTM25E8HM4
Type	T50RTM25E
Color	Gray (GY)
Features and Benefits	<ul style="list-style-type: none">• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.• Initial fir tree serves as a locating feature for assistance in blind assembly applications.• Disc feature provides anti-rattle protection in high vibration applications.
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
Fixation Method (FF)	Fir Tree
Identification Plate Position	none
Releasable Closure (Yes/No)	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Fir Tree Push Mount Ties, 8.3" Long, .25" - .28" Mounting Hole, PA66HIRHS, Grey, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	222 N
Length L (imperial)	8.0 "
Length L (metric)	213.8 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	50.8 mm
Disc Diameter (imperial)	0.5 "
Disc Diameter (metric)	12.6 mm
Panel Thickness max. (imperial)	0.5 "
Panel Thickness max. (metric)	13.9 mm
Panel Thickness min. (imperial)	0.09 "
Panel Thickness min. (metric)	2.3 mm
Mounting Hole Diameter D (imperial)	0.28 "
Mounting Hole Diameter D (metric)	7.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	1000
Carton Quantity	5000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +212 °F (-40 °C to +100 °C)
ROHS Conformity	Yes