

## T5D087510H4



**Article Number:** 211-00116

**P Clamp, .5" Width, .875" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 500/pkg**



### Base Data

<b>Local Order Number</b>	T5D087510H4
<b>Type</b>	T5D0875
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Easily guide and locate wire and cables up to 1.5" in diameter.</li> <li>• Designed with a radiused edge to prevent chaffing and cutting into insulation.</li> </ul>
<b>Product Description</b>	HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1.5" bundle diameters.
<b>Fixation Method (FF)</b>	screw-hole
<b>Variant</b>	Closed
<b>Short Description</b>	P Clamp, .5" Width, .875" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 500/pkg

### Product Dimensions

<b>Width W (imperial)</b>	0.5 "
<b>Width W (metric)</b>	12.7 mm
<b>Bundle Diameter max (imperial)</b>	0.87 "
<b>Bundle Diameter max (metric)</b>	22.22 mm
<b>Mounting Hole Diameter D (imperial)</b>	0.203 "
<b>Mounting Hole Diameter D (metric)</b>	5.1 mm
<b>Wall Thickness WT (imperial)</b>	.050 "
<b>Wall Thickness WT (metric)</b>	1.3 mm
<b>Mounting Hole Centers (imperial)</b>	0.845 "
<b>Mounting Hole Centers (metric)</b>	21.46 mm

### Logistics and Packaging

<b>Quantity per</b>	bag
<b>Package Quantity</b>	500 Pieces

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes

