

Article Number: 594-11789

Laser Tag Self-Laminating Label, .65" X .20", 480 Per Sheet, Polyester, White, 5000/pkg



Base Data

Local Order Number TAG11L-789

Type TAG11L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Color of Print Black (BK)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Paper Format Letter

Short Description Laser Tag Self-Laminating Label, .65" X .20", 480 Per Sheet, Polyester, White, 5000/pkg

Product Dimensions

Length L (imperial) 0.2 "

Length L (metric) 5.08 mm

Width W (imperial) 0.65 "

Width W (metric) 16.5 mm

Height H (imperial) 0.2 "

Height H (metric) 5.08 mm

Height H2 (imperial) 0.2 "

Height H2 (metric) 5.08 mm

Horizontal Repeat HR (metric) 19.05 mm

Horizontal Repeat HR (imperial) .750 "

Print Method Laser

Thickness T (Metric) 64.0 µm

Thickness of Foil (TF) 64 µm

Vertical Repeat VR (imperial) 0.2 "

Vertical Repeat VR (metric) 5.08 mm

Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 5000

Package Quantity	5000
Carton Quantity	5000 Pieces
Labels per Column	48
Labels per Row	10
Labels per Sheet	480
Sheets per Pack	11

Material and Specifications

Material	Type 789, Polyethylenterephthalat (PET)
Material Shortcut	789
Adhesive	Acrylic
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
ROHS Conformity	Yes