HellermannTyton

TAG13T4-822

Article Number: 596-13822

Thermal Transfer Label, .75" X .25", 4 Across, Polyester, White, 10000/RL

HellermannTyton

RoHS

Base Data

Local Order Number	TAG13T4-822
Туре	TAG13T4
Color	White (WH)
Features and Benefits	 Thermal transfer labels are made with high performance materials for long term industrial applications. Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, .75" X .25", 4 Across, Polvester, White, 10000/RL

Product Dimensions

Width W (imperial)	0.75 "
Width W (metric)	19.05 mm
Height H (imperial)	0.25 "
Height H (metric)	6.35 mm
Horizontal Repeat HR (metric)	19.05 mm
Horizontal Repeat HR (imperial)	.75 "
Print Method	Thermal Transfer
Vertical Repeat VR (imperial)	0.35 "
Vertical Repeat VR (metric)	8.89 mm
Width of Liner WL (imperial)	3.35 "
Width of Liner WL (metric)	85.09 mm

Logistics and Packaging

roll
10000
10000
10000 Pieces
4

Material and Specifications

Material Type 822, Polyester, white (WH)

Material Shortcut 822

Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
ROHS Conformity	Yes
Certification / Specification	UL-Recognized
UL Recognized (US and Canada)	Yes

© HellermannTyton 2014