

Article Number: 596-00007

Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL



### Base Data

<b>Local Order Number</b>	TAG22T3-100B
<b>Type</b>	TAG22T3
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.</li> <li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li> <li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li> <li>• HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.</li> </ul>
<b>Color Marking Field</b>	White (WH)
<b>Product Description</b>	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
<b>For Wire Type</b>	4 Pair UTP / RG6 & RG59 Coax
<b>Short Description</b>	Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL

### Product Dimensions

<b>Width W (imperial)</b>	1.0 "
<b>Width W (metric)</b>	25.4 mm
<b>Height H (imperial)</b>	0.5 "
<b>Height H (metric)</b>	12.7 mm
<b>Height H2 (imperial)</b>	1.43 "
<b>Height H2 (metric)</b>	36.5 mm
<b>Bundle Diameter min (imperial)</b>	0.137 "
<b>Bundle Diameter min (metric)</b>	3.5 mm
<b>Bundle Diameter max (imperial)</b>	0.29 "
<b>Bundle Diameter max (metric)</b>	7.6 mm
<b>Horizontal Repeat HR (metric)</b>	27.3 mm
<b>Horizontal Repeat HR (imperial)</b>	1.075 "
<b>Print Method</b>	Thermal Transfer
<b>Thickness T (Metric)</b>	25 µm
<b>Vertical Repeat VR (imperial)</b>	1.62 "
<b>Vertical Repeat VR (metric)</b>	41.28 mm
<b>Width of Liner WL (imperial)</b>	3.35 "
<b>Width of Liner WL (metric)</b>	85.09 mm

## Logistics and Packaging

---

<b>Quantity per</b>	roll
<b>Package Quantity (imperial)</b>	5000
<b>Package Quantity</b>	5000
<b>Labels per Row</b>	3

## Material and Specifications

---

<b>Material</b>	Type 100, self laminating Vinyl, white (WH)
<b>Material Shortcut</b>	100B
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40 °F to +194 °F (-40 °C to +90 °C)
<b>Operating Temperature</b>	-40 °F to +194 °F (-40 °C to +90 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL-Recognized