

Article Number: 595-25100

Dot Matrix, Self-Laminating Label, .75" X .50" X 1.75", 9 Across, White, 5000/pkg



### Base Data

Local Order Number TAG25-100

Type TAG25

Color White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

Color Marking Field White (WH)

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

Mounting method Identification ETIM Pasting / Stick

Self adhesive (Yes/No) Yes

Variant Adhesive label

Short Description Dot Matrix, Self-Laminating Label, .75" X .50" X 1.75", 9 Across, White, 5000/pkg

With label space ETIM Yes

### Product Dimensions

Length L (imperial) 1.75 "

Length L (metric) 44.5 mm

Core diameter from / to 5.1 - 10.10 mm

Width W (imperial) 0.75 "

Width W (metric) 19.05 mm

Height H (imperial) 0.5 "

Height H (metric) 12.7 mm

Height H2 (imperial) 1.75 "

Height H2 (metric) 44.5 mm

Bundle Diameter min (imperial) 0.2 "

Bundle Diameter min (metric) 5.10 mm

Bundle Diameter max (imperial) 0.4 "

Bundle Diameter max (metric) 10.10 mm

Outside Diameter min. (imperial) 0.2 "

Outside Diameter min. (metric) 5.1 mm

Outside Diameter max. (imperial) 0.39 "

Outside Diameter max. (metric) 10.10 mm

Horizontal Repeat HR (metric) 22.86 mm

<b>Horizontal Repeat HR (imperial)</b>	.900 "
<b>Print Method</b>	Dot-Matrix
<b>Thickness T (Metric)</b>	75.0 µm
<b>Thickness of Foil (TF)</b>	75 µm
<b>Vertical Repeat VR (imperial)</b>	2.0 "
<b>Vertical Repeat VR (metric)</b>	50.80 mm
<b>Width of Liner WL (imperial)</b>	8.9 "
<b>Width of Liner WL (metric)</b>	228.60 mm

## Logistics and Packaging

---

<b>Quantity per</b>	pack
<b>Package Quantity</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Labels per Column</b>	9
<b>Labels per Row</b>	9
<b>Weight (Metric)</b>	0.27 kg

## Material and Specifications

---

<b>Material</b>	Type 100, self laminating Vinyl, white (WH)
<b>Material Shortcut</b>	100
<b>Adhesive</b>	Acrylic
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive Operating Temperature</b>	-51 °F to +200 °F (-46 °C to +93 °C)
<b>Operating Temperature</b>	-51 °F to +200 °F (-46 °C to +93 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL-Recognized