

Article Number: 595-06100

Dot Matrix, Self-Laminating Label, 2.0" X 1.0" X 3.19", 4 Across, White, 2500/pkg



### Base Data

Local Order Number TAG6-100

Type TAG6

Color White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

Color Marking Field White (WH)

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

Mounting method Identification ETIM Pasting / Stick

Self adhesive (Yes/No) Yes

Variant Adhesive label

Short Description Dot Matrix, Self-Laminating Label, 2.0" X 1.0" X 3.19", 4 Across, White, 2500/pkg

With label space ETIM Yes

### Product Dimensions

Length L (imperial) 3.75 "

Length L (metric) 95.3 mm

Core diameter from / to 11.1 - 22.20 mm

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Height H2 (imperial) 3.75 "

Height H2 (metric) 95.3 mm

Bundle Diameter min (imperial) 0.43 "

Bundle Diameter min (metric) 11.10 mm

Bundle Diameter max (imperial) 0.87 "

Bundle Diameter max (metric) 22.20 mm

Outside Diameter min. (imperial) 0.43 "

Outside Diameter min. (metric) 11.1 mm

Outside Diameter max. (imperial) 0.87 "

Outside Diameter max. (metric) 22.20 mm

Horizontal Repeat HR (metric) 50.80 mm

<b>Horizontal Repeat HR (imperial)</b>	2.000 "
<b>Print Method</b>	Dot-Matrix
<b>Thickness T (Metric)</b>	75.0 µm
<b>Thickness of Foil (TF)</b>	75 µm
<b>Vertical Repeat VR (imperial)</b>	4.0 "
<b>Vertical Repeat VR (metric)</b>	101.6 mm
<b>Width of Liner WL (imperial)</b>	8.9 "
<b>Width of Liner WL (metric)</b>	228.60 mm

## Logistics and Packaging

---

<b>Quantity per</b>	pack
<b>Package Quantity (imperial)</b>	2500
<b>Package Quantity</b>	2500
<b>Carton Quantity</b>	2500 Pieces
<b>Labels per Column</b>	4
<b>Labels per Row</b>	4
<b>Weight (Metric)</b>	1 kg

## Material and Specifications

---

<b>Material</b>	Type 100, self laminating Vinyl, white (WH)
<b>Material Shortcut</b>	100
<b>Adhesive</b>	Acrylic
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive Operating Temperature</b>	-51 °F to +200 °F (-46 °C to +93 °C)
<b>Operating Temperature</b>	-51 °F to +200 °F (-46 °C to +93 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL-Recognized