

TAG62L-788

Article Number: 594-62788

Laser Tag Label, 1.5" X .37", 125 Per Sheet, Polyester, White, 1000/pkg



Base Data

Local Order Number	TAG62L-788
Type	TAG62L
Color	White (WH)
Features and Benefits	• LaserTags are sheet fed for easy loading and fast printing. • LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing. • LaserTags are printable using toner for long term UV exposure. • LaserTags come in a variety of label sizes and types to fit most applications.
Product Description	LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.
Paper Format	Letter
Short Description	Laser Tag Label, 1.5" X .37", 125 Per Sheet, Polyester, White, 1000/pkg

Product Dimensions

Length L (imperial)	0.375 "
Length L (metric)	9.52 mm
Width W (imperial)	1.5 "
Width W (metric)	31.75 mm
Height H (imperial)	0.37 "
Height H (metric)	9.52 mm
Horizontal Repeat HR (metric)	31.75 mm
Horizontal Repeat HR (imperial)	1.500 "
Print Method	Laser
Thickness T (Metric)	64.0 µm
Thickness of Foil (TF)	64 µm
Vertical Repeat VR (imperial)	0.37 "
Vertical Repeat VR (metric)	9.52 mm

Logistics and Packaging

Quantity per	pack
Package Quantity (imperial)	1000
Package Quantity	1000
Carton Quantity	1000 Pieces
Labels per Column	25

Labels per Row	5
Labels per Sheet	125
Sheets per Pack	8
Weight (Metric)	0.45 kg

Material and Specifications

Material	Type 789, Polyethylenterephthalat (PET)
Material Shortcut	789
Adhesive	Acrylic
Shortcut Adhesive	Acryl
Operating Temperature	-40 °F to +199 °F (-40 °C to +93 °C)
ROHS Conformity	Yes