

TAG66L-789

Article Number: 594-66789

Laser Tag Label, 3.6" X .375", 50 Per Sheet, Polyester, White, 1000/pkg



Base Data

Local Order Number TAG66L-789

Type TAG66L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Color Marking Field White (WH)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Paper Format Letter

Short Description Laser Tag Label, 3.6" X .375", 50 Per Sheet, Polyester, White, 1000/pkg

Product Dimensions

Length L (imperial) 0.375 "

Length L (metric) 9.52 mm

Width W (imperial) 3.59 "

Width W (metric) 91.4 mm

Height H (imperial) 0.375 "

Height H (metric) 9.52 mm

Horizontal Repeat HR (metric) 91.40 mm

Horizontal Repeat HR (imperial) 3.600 "

Print Method Laser

Thickness T (Metric) 35.0 µm

Vertical Repeat VR (imperial) 0.375 "

Vertical Repeat VR (metric) 9.52 mm

Width of Liner WL (imperial) 8.5 "

Width of Liner WL (metric) 215.00 mm

Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 1000

Package Quantity 1000

Carton Quantity	1000
Labels per Column	25
Labels per Row	2
Labels per Sheet	50
Sheets per Pack	20

Material and Specifications

Material	Type 789, Polyethylenterephthalat (PET)
Material Shortcut	789
Adhesive	Acrylic
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +302 °F (-40 °C to +150 °C)
Operating Temperature	-40 °F to +300 °F (-40 °C to +149 °C)
ROHS Conformity	Yes