

TAG68L-789

Article Number: 594-68789

Laser Tag Label, 3.8" X .275", 70 Per sheet, Polyester, White, 1000/pkg



Base Data

Local Order Number TAG68L-789

Type TAG68L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Paper Format Letter

Short Description Laser Tag Label, 3.8" X .275", 70 Per sheet, Polyester, White, 1000/pkg

Product Dimensions

Length L (imperial) 0.275 "

Length L (metric) 6.98 mm

Width W (imperial) 3.8 "

Width W (metric) 96.5 mm

Height H (imperial) 0.275 "

Height H (metric) 6.98 mm

Horizontal Repeat HR (metric) 96.50 mm

Horizontal Repeat HR (imperial) 3.800 "

Print Method Laser

Thickness T (Metric) 64.0 µm

Thickness of Foil (TF) 64 µm

Vertical Repeat VR (imperial) 0.275 "

Vertical Repeat VR (metric) 6.98 mm

Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 2500

Package Quantity 2500

Carton Quantity 2500

Labels per Column 35

Labels per Row 2

Labels per Sheet 70

Sheets per Pack 36

Material and Specifications

Material Type 789, Polyethylenterephthalat (PET)

Material Shortcut 789

Adhesive Acrylic

Shortcut Adhesive Acryl

Operating Temperature -40 °F to +302 °F (-40 °C to +150 °C)

ROHS Conformity Yes