# HellermannTyton

#### TAG73T1-795

Article Number: 596-73795

Thermal Transfer Label, 2.0" X 1.0", 1 Across, Polyester, Silver, 3000/RL





#### **Base Data**

Local Order Number TAG73T1-795

Type TAG73T1

Color Silver (SR)

Features and Benefits • Thermal transfer labels are made with high performance materials for long term industrial applications.

· Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the

need to be dedicated to one printer model.

• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester,

cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product

is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 2.0" X 1.0", 1 Across, Polyester, Silver, 3000/RL

### **Product Dimensions**

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Horizontal Repeat HR (metric) 25.4 mm

Horizontal Repeat HR (imperial) 1.0 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 1.125 "

Vertical Repeat VR (metric) 28.57 mm

Width of Liner WL (imperial) 2.2 "

Width of Liner WL (metric) 55.83 mm

## **Logistics and Packaging**

Quantity per roll

Package Quantity (imperial) 3000

Package Quantity 3000

Carton Quantity 3000 Pieces

Labels per Row 1

Weight (Metric) 0.341 kg

## **Material and Specifications**

Material Type 795, Polyester, silver matt (SR)

Material Shortcut 795

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature  $-40 \, ^{\circ}\text{F}$  to +300  $^{\circ}\text{F}$  (-40  $^{\circ}\text{C}$  to +149  $^{\circ}\text{C}$ )

**Operating Temperature**  $-40 \,^{\circ}\text{F} \text{ to } +300 \,^{\circ}\text{F} \text{ (-}40 \,^{\circ}\text{C to } +149 \,^{\circ}\text{C)}$ 

ROHS Conformity Yes

Certification / Specification UL-Recognized

UL Recognized (US and Canada) Yes