

## TAG73T1-DTH

Article Number: 596-00038

Thermal Transfer Label, 2.0" X 1.0", 1 Across, DTH, White, 3000/RL



### Base Data

Local Order Number TAG73T1-DTH

Type TAG73T1

Color White (WH)

**Features and Benefits**

- Thermal transfer labels are made with high performance materials for long term industrial applications.
- Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.
- The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

**Product Description** Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.

**Short Description** Thermal Transfer Label, 2.0" X 1.0", 1 Across, DTH, White, 3000/RL

### Product Dimensions

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 1.0 "

Height H (metric) 25.4 mm

Horizontal Repeat HR (metric) 25.4 mm

Horizontal Repeat HR (imperial) 1.0 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 1.125 "

Vertical Repeat VR (metric) 28.57 mm

Width of Liner WL (imperial) 2.2 "

Width of Liner WL (metric) 55.83 mm

### Logistics and Packaging

Quantity per roll

Package Quantity (imperial) 3000

Package Quantity 3000

Labels per Row 1

### Material and Specifications

Material Type DTH, Durattach white (WH)

Material Shortcut DTH

Adhesive Acrylic

**Shortcut Adhesive** Acryl

**Adhesive Operating Temperature** -40 °F to +140 °F (-40 °C to +60 °C)

**Operating Temperature** -40 °F to +140 °F (-40 °C to +60 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL-Recognized