# HellermannTyton

#### TAG75T1-822

Article Number: 596-00019

Thermal Transfer Label, 2.0" X .625", 1 Across, Polyester, White, 2000/RL



RoHS

#### **Base Data**

Local Order Number TAG75T1-822

Type TAG75T1

Color White (WH)

Features and Benefits • Thermal transfer labels are made with high performance materials for long term industrial applications.

· Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the

need to be dedicated to one printer model.

• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester,

cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product

is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 2.0" X.625", 1 Across, Polyester, White, 2000/RL

#### **Product Dimensions**

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 0.625 "

Height H (metric) 15.87 mm

Horizontal Repeat HR (metric) 50.8 mm

Horizontal Repeat HR (imperial) 2.0 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 0.75 "

Vertical Repeat VR (metric) 19.05 mm

Width of Liner WL (imperial) 2.12 "

Width of Liner WL (metric) 53.8 mm

## **Logistics and Packaging**

Quantity per roll

Package Quantity (imperial) 2000

Package Quantity 2000

Labels per Row

### **Material and Specifications**

Material Type 822, Polyester, white (WH)

Material Shortcut 822

Adhesive Acrylic

Adhesive Operating Temperature  $\,$  -40 °F to +302 °F (-40 °C to +150 °C)

Operating Temperature  $\,$  -40 °F to +302 °F (-40 °C to +150 °C)

ROHS Conformity Yes

Certification / Specification UL-Recognized

UL Recognized (US and Canada) Yes