

TAG78T1-795

Article Number: 596-78795

Thermal Transfer Label, 3.0" X 4.0", 1 Across, Polyester, Silver , 500/RL



Base Data

Local Order Number	TAG78T1-795
Type	TAG78T1
Color	Silver (SR)
Features and Benefits	<ul style="list-style-type: none">• Thermal transfer labels are made with high performance materials for long term industrial applications.• Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, 3.0" X4.0", 1 Across, Polyester, Silver , 500/RL

Product Dimensions

Width W (imperial)	3.0 "
Width W (metric)	76.2 mm
Height H (imperial)	4.0 "
Height H (metric)	101.6 mm
Horizontal Repeat HR (metric)	76.2 mm
Horizontal Repeat HR (imperial)	3.0 "
Print Method	Thermal Transfer
Vertical Repeat VR (imperial)	4.12 "
Vertical Repeat VR (metric)	104.7 mm
Width of Liner WL (imperial)	3.12 "
Width of Liner WL (metric)	79.2 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	500
Package Quantity	500
Labels per Row	1

Material and Specifications

Material	Type 795, Polyester, silver matt (SR)
Material Shortcut	795
Adhesive	Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

ROHS Conformity Yes

Certification / Specification UL-Recognized

UL Recognized (US and Canada) Yes