

TAG79T1-795

Article Number: 596-79795

Thermal Transfer Label, 4.0" X 2.0", 1 Across, Polyester, Silver, 500/RL



Base Data

| | |
|-----------------------|--|
| Local Order Number | TAG79T1-795 |
| Type | TAG79T1 |
| Color | Silver (SR) |
| Features and Benefits | <ul style="list-style-type: none">• Thermal transfer labels are made with high performance materials for long term industrial applications.• Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy. |
| Product Description | Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core. |
| Short Description | Thermal Transfer Label, 4.0" X2.0", 1 Across, Polyester, Silver, 500/RL |

Product Dimensions

| | |
|---------------------------------|------------------|
| Width W (imperial) | 4.0 " |
| Width W (metric) | 101.6 mm |
| Height H (imperial) | 2.0 " |
| Height H (metric) | 50.8 mm |
| Horizontal Repeat HR (metric) | 101.6 mm |
| Horizontal Repeat HR (imperial) | 4.0 " |
| Print Method | Thermal Transfer |
| Vertical Repeat VR (imperial) | 2.12 " |
| Vertical Repeat VR (metric) | 53.97 mm |
| Width of Liner WL (imperial) | 4.25 " |
| Width of Liner WL (metric) | 107.9 mm |

Logistics and Packaging

| | |
|-----------------------------|------------|
| Quantity per | roll |
| Package Quantity (imperial) | 500 |
| Package Quantity | 500 |
| Carton Quantity | 500 Pieces |
| Labels per Row | 1 |
| Weight (Metric) | 1.25 kg |

Material and Specifications

| | |
|----------|---------------------------------------|
| Material | Type 795, Polyester, silver matt (SR) |
|----------|---------------------------------------|

Material Shortcut 795

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

Operating Temperature -40 °F to +300 °F (-40 °C to +149 °C)

ROHS Conformity Yes

Certification / Specification UL-Recognized

UL Recognized (US and Canada) Yes