

## TAGPP2-788C

Article Number: 594-00002

Laser Tag Label, .66" X .31", 360 Per Sheet, Polyester, Clear, 1000/pkg



### Base Data

Local Order Number TAGPP2-788C

Type TAGPP2

Color Clear (CL)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Paper Format Letter

Short Description Laser Tag Label, .66" X .31", 360 Per Sheet, Polyester, Clear, 1000/pkg

### Product Dimensions

Length L (imperial) 0.33 "

Length L (metric) 8.38 mm

Width W (imperial) 0.66 "

Width W (metric) 16.7 mm

Height H (imperial) 0.33 "

Height H (metric) 8.38 mm

Horizontal Repeat HR (metric) 16.70 mm

Horizontal Repeat HR (imperial) .660 "

Print Method Laser

Vertical Repeat VR (imperial) 0.33 "

Vertical Repeat VR (metric) 8.38 mm

### Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 1000

Package Quantity 1000

Carton Quantity 1000

Labels per Column 30

Labels per Row 12

Labels per Sheet 360

## Material and Specifications

---

<b>Material</b>	Type 788C, Polyester, clear (CR)
<b>Material Shortcut</b>	788C
<b>Adhesive</b>	Acrylic
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive Operating Temperature</b>	-40 °F to +199 °F (-40 °C to +93 °C)
<b>Operating Temperature</b>	-40 °F to +199 °F (-40 °C to +93 °C)
<b>ROHS Conformity</b>	Yes