

TCWM12



Article Number: 598-00271

Handi-Pak, 15 Markers Each of A-Z, 21 Markers Blank, 8 Markers "+" and 7 Markers "-", White, 1/pkg



Base Data

Local Order Number TCWM12

Type TCWM12

Color White (WH)

- Features and Benefits**
- Handi-Paks booklets fit in a pocket for easy transport and access.
 - A single marker can be removed at the top of each label so that the terminal block can be marked and the remaining label can be used to mark the associated wire connected to the terminal.
 - Markers are kitted on each page so that any marker can be removed without affecting the other markers on the page.
 - Markers have a micro-perforation in the middle of each marker so that they can be broken into two pieces for use on small gauge wires, eliminating waste and reducing costs.

Color of Print Black (BK)

Product Description Handi-Paks are convenient pocket sized books that contain pages of black, pre-printed legends on a white background. The legends are printed on a plastic coated cloth label that remains flexible for use in identifying wires and cables. A strong adhesive assures long lasting identification on small wires, cables or anything requiring permanent or temporary identification.

Short Description Handi-Pak, 15 Markers Each of A-Z, 21 Markers Blank, 8 Markers "+" and 7 Markers "-", White, 1/pkg

Product Dimensions

Length L (imperial) 1.625 "

Length L (metric) 41.27 mm

Core diameter from / to 2.54 - 9.52 mm

Width W (imperial) 0.25 "

Width W (metric) 6.35 mm

Height H (imperial) 1.625 "

Height H (metric) 41.27 mm

Outside Diameter min. (imperial) 0.1 "

Outside Diameter min. (metric) 2.54 mm

Outside Diameter max. (imperial) 0.375 "

Outside Diameter max. (metric) 9.52 mm

Logistics and Packaging

Quantity per book

Package Quantity (imperial) 1

Package Quantity 1

Labels per Column 3

Labels per Row 15

Labels per Sheet 45

Material and Specifications

Material	Vinyl Cloth (TYHC)
Material Shortcut	TYHC
Adhesive	Rubber
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +248 °F (-40 °C to +120 °C)
Operating Temperature	-40 °F to +248 °F (-40 °C to +120 °C)
ROHS Conformity	Yes