

## TCWM13



Article Number: 598-00272

Handi-Pak, 45 Markers Each of +,AC,DC,-, 33 Each of POS, NEG, GND, 27 of NEUT; 21 Each of SPARE and BLANK, White, 1/pkg



### Base Data

**Local Order Number** TCWM13

**Type** TCWM13

**Color** White (WH)

- Features and Benefits**
- Handi-Paks booklets fit in a pocket for easy transport and access.
  - A single marker can be removed at the top of each label so that the terminal block can be marked and the remaining label can be used to mark the associated wire connected to the terminal.
  - Markers are kitted on each page so that any marker can be removed without affecting the other markers on the page.
  - Markers have a micro-perforation in the middle of each marker so that they can be broken into two pieces for use on small gauge wires, eliminating waste and reducing costs.

**Color of Print** Black (BK)

**Product Description** Handi-Paks are convenient pocket sized books that contain pages of black, pre-printed legends on a white background. The legends are printed on a plastic coated cloth label that remains flexible for use in identifying wires and cables. A strong adhesive assures long lasting identification on small wires, cables or anything requiring permanent or temporary identification.

**Short Description** Handi-Pak, 45 Markers Each of +,AC,DC,-, 33 Each of POS, NEG, GND, 27 of NEUT; 21 Each of SPARE and BLANK, White, 1/pkg

### Product Dimensions

**Length L (imperial)** 1.625 "

**Length L (metric)** 41.27 mm

**Core diameter from / to** 2.54 - 9.52 mm

**Width W (imperial)** 0.25 "

**Width W (metric)** 6.35 mm

**Height H (imperial)** 1.625 "

**Height H (metric)** 41.27 mm

**Outside Diameter min. (imperial)** 0.1 "

**Outside Diameter min. (metric)** 2.54 mm

**Outside Diameter max. (imperial)** 0.375 "

**Outside Diameter max. (metric)** 9.52 mm

### Logistics and Packaging

**Quantity per** book

**Package Quantity (imperial)** 1

**Package Quantity** 1

**Labels per Column** 3

**Labels per Row** 15

## Material and Specifications

---

<b>Material</b>	Vinyl Cloth (TYHC)
<b>Material Shortcut</b>	TYHC
<b>Adhesive</b>	Rubber
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive Operating Temperature</b>	-40 °F to +248 °F (-40 °C to +120 °C)
<b>Operating Temperature</b>	-40 °F to +248 °F (-40 °C to +120 °C)
<b>ROHS Conformity</b>	Yes