

TELS-13



Article Number: 111-32108

Extended Length Tie, POM, Black, 10-13.5" straps and 10 heads/pkg

 RoHS

Base Data

Local Order Number	TELS-13
Type	TELS-13
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Continuous strap and separate heads allow for any bundle diameter, eliminating waste.</li><li>• Smooth strap prevents cable damage.</li><li>• UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.</li></ul>
Product Description	HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.
Fixation Method (FF)	None
Releasable Closure (Yes/No)	No
Tie Closure	steel pawl
Variant	Extended Length
Short Description	Extended Length Tie, POM, Black, 10-13.5" straps and 10 heads/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	250.0 lbs
Minimum Tensile Strength (N)	1112.0 N
Length L (imperial)	13.5 "
Length L (metric)	343.0 mm
Width W (imperial)	0.5 "
Width W (metric)	12.7 mm
Width W2 (imperial)	0.8 "
Width W2 (metric)	20.3 mm
Height H (imperial)	0.49 "
Height H (metric)	12.4 mm
Thickness T (imperial)	0.06 "
Thickness T (Metric)	1.52 mm

Logistics and Packaging

Quantity per	pack
Package Quantity	10
Carton Quantity	500

Material and Specifications

<b>Material</b>	Polyacetal (POM)
<b>Material Shortcut</b>	POM
<b>Material Cable Tie</b>	Polyacetal (POM)
<b>Flammability</b>	UL94 HB
<b>Material Head</b>	Polyacetal (POM)
<b>Material Spacer</b>	Polypropylene, UV-resistant (PPW)
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes