

## TELS-H



**Article Number:** 111-31000

**Extended Length Tie Heads, POM, Black, 25/pkg**



### Base Data

**Local Order Number** TELS-H

**Type** TELS-H

**Color** Black (BK)

- Features and Benefits**
- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
  - Smooth strap prevents cable damage.
  - UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

**Product Description** HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

**Fixation Method (FF)** None

**Releasable Closure (Yes/No)** No

**Tie Closure** steel pawl

**Variant** Extended Length

**Short Description** Extended Length Tie Heads, POM, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 250.0 lbs

**Length L (imperial)** 0.62 "

**Length L (metric)** 15.75 mm

**Width W (imperial)** 0.8 "

**Width W (metric)** 20.3 mm

**Width W2 (imperial)** 0.8 "

**Width W2 (metric)** 20.3 mm

**Height H (imperial)** 0.49 "

**Height H (metric)** 12.4 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 25

**Carton Quantity** 25 Pieces

**Weight (Metric)** 1.2 kg

### Material and Specifications

**Material** Polyacetal (POM)

**Material Shortcut** POM

**Material Cable Tie** Polyacetal (POM)  
**Flammability** UL94 HB  
**Material Head** Polyacetal (POM)  
**Material Spacer** Polypropylene (PP)  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes