

## TM1SF0M4



**Article Number:** 151-40101

**Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, Black, 1000/pkg**



### Base Data

**Local Order Number** TM1SF0M4

**Type** TM1SF

**Color** Black (BK)

- Features and Benefits**
- Push Mounts, when used with standard cable ties, provide a permanent bundling solution.
  - The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Product Description** HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

**Fixation Method (FF)** with Arrowhead / Push Mount (Mounts)

**For Ties** T18 to T50

**Short Description** Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, Black, 1000/pkg

### Product Dimensions

**Length L (imperial)** 0.62 "

**Length L (metric)** 15.8 mm

**Width W (imperial)** 0.4 "

**Width W (metric)** 10.2 mm

**Cable Tie Width Max (imperial)** 0.2 "

**Cable Tie Width max. (metric)** 5.0 mm

**Height H (imperial)** 0.18 "

**Height H (metric)** 4.6 mm

**Height H2 (imperial)** 0.18 "

**Height H2 (metric)** 4.6 mm

**Panel Thickness max. (imperial)** 0.13 "

**Panel Thickness max. (metric)** 3.3 mm

**Panel Thickness min. (imperial)** 0.13 "

**Panel Thickness min. (metric)** 3.40 mm

**Mounting Hole Diameter D (imperial)** 0.25 "

**Mounting Hole Diameter D (metric)** 6.35 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 1000

**Carton Quantity** 20000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes