

TM1SF10C2



Article Number: 151-40119

Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg



Base Data

Local Order Number TM1SF10C2

Type TM1SF

Color White (WH)

Features and Benefits

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution.
- The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

Fixation Method (FF) with Arrowhead / Push Mount (Mounts)

For Ties T18 to T50

Short Description Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg

Product Dimensions

Length L (imperial) 0.62 "

Length L (metric) 15.8 mm

Width W (imperial) 0.4 "

Width W (metric) 10.2 mm

Cable Tie Width Max (imperial) 0.2 "

Cable Tie Width max. (metric) 5.0 mm

Height H (imperial) 0.18 "

Height H (metric) 4.6 mm

Height H2 (imperial) 0.18 "

Height H2 (metric) 4.6 mm

Panel Thickness max. (imperial) 0.13 "

Panel Thickness max. (metric) 3.3 mm

Panel Thickness min. (imperial) 0.13 "

Panel Thickness min. (metric) 3.40 mm

Mounting Hole Diameter D (imperial) 0.25 "

Mounting Hole Diameter D (metric) 6.35 mm

Mounting Hole Diameter D max (imperial) 0.28 "

Mounting Hole Diameter D max 6.3 mm
(metric)

Logistics and Packaging

Quantity per pc

Package Quantity 100

Carton Quantity 15000 Pieces

Weight (Metric) 1 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes