

TM1SF9M4



Article Number: 151-40103

Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, Natural, 1000/pkg



Base Data

Local Order Number TM1SF9M4

Type TM1SF

Color Natural (NA)

Features and Benefits

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution.
- The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

Fixation Method (FF) with Arrowhead / Push Mount (Mounts)

For Ties T18 to T50

Short Description Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, Natural, 1000/pkg

Product Dimensions

Length L (imperial) 0.62 "

Length L (metric) 15.8 mm

Width W (imperial) 0.4 "

Width W (metric) 10.2 mm

Cable Tie Width Max (imperial) 0.2 "

Cable Tie Width max. (metric) 5.0 mm

Height H (imperial) 0.18 "

Height H (metric) 4.6 mm

Height H2 (imperial) 0.18 "

Height H2 (metric) 4.6 mm

Panel Thickness max. (imperial) 0.13 "

Panel Thickness max. (metric) 3.3 mm

Panel Thickness min. (imperial) 0.13 "

Panel Thickness min. (metric) 3.40 mm

Mounting Hole Diameter D (imperial) 0.25 "

Mounting Hole Diameter D (metric) 6.35 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Carton Quantity 20000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes