HellermannTyton

TSRP3I-8A



Article Number: 250-63801

TSRP 1-3/4" Power Rated Raceway, 8' Long, PVC, Ivory, 160ft/Carton

RoHS

Base Data

Local Order Number	TSRP3I-8A
Туре	TSRP3-8A
Color	lvory (IV)
Features and Benefits	 Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables. An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration.
	 Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Product Description	HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems.
Short Description	TSRP 1-3/4" Power Rated Raceway, 8' Long, PVC, Ivory, 160ft/Carton

Product Dimensions

Length L (imperial)	8.0 ft
Length L (metric)	2.44 m
Width W (imperial)	1.75 "
Width W (metric)	44.45 mm
Height H (imperial)	1.0 "
Height H (metric)	25.4 mm

Logistics and Packaging

Quantity per	box
Package Quantity (imperial)	160
Package Quantity	118.3
Carton Quantity	160

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
ROHS Conformity	Yes
UL Listed (US)	Yes