



TT822OUTSM



Article Number: 556-00145

Thermal Transfer Ribbon, 4.33" X 299', .50" Core, 822 Resin, Black, 1/EA

 RoHS

Base Data

Local Order Number	TT822OUTSM
Type	TT822OUTSM
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Ribbons are resin based for the best print durability.</li><li>• Ribbons are available to fit all HellermannTyton printers for easy resupply.</li><li>• Ribbons are available in colors for maximizing design printing capabilities.</li><li>• Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.</li></ul>
Product Description	HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.
Variant	Coloured ribbon
Short Description	Thermal Transfer Ribbon, 4.33" X 299', .50" Core, 822 Resin, Black, 1/EA

Product Dimensions

Length L (imperial)	242.0 ft
Length L (metric)	74.0 m
Width W (imperial)	4.33 "
Width W (metric)	110.0 mm
Print Method	Thermal Transfer
Recommended Material	100/250/336/822/822C/795/799

Logistics and Packaging

Quantity per	EA
Package Quantity (imperial)	1
Package Quantity	1
Carton Quantity	1
Labels per Column	1
Reel Length (metric)	74 m
Reel Length (imperial)	242.0 ft

Material and Specifications

Material	Polyester Film
Material Shortcut	PET
Operating Temperature	+40 °F to +300 °F (+4 °C to +82 °C)
ROHS Conformity	Yes

