

## TYHC4

Article Number: 598-00024

Handi-Card, .25" X 1.5", Solid #4, 36 Per Card, White, 25/pkg



### Base Data

Local Order Number TYHC4

Type TYHC4

Color White (WH)

- Features and Benefits**
- Handi Cards have a split backing so that a portion of the liner can be removed to expose the markers for easy dispensing.
  - Handi-Cards are kitted on the card so that specific markers can be removed without affecting the other markers on the card.
  - Markers are pre-printed so no additional post printing is required, saving time and money.
  - Label material is a conformable cloth that ensures markers stay on wires and cables for the life of the application.

**Product Description** HellermannTyton Handi-Cards are easy release pre-printed cloth markers, on a plastic card, with a strong adhesive for a long lasting bond on wire and cable. The markers are available in Solid format where each marker on the card contains the same legend and Sequence format where each marker on the card contains a different number or letter which is usually printed in sequence from lowest to highest in sort order.

**Short Description** Handi-Card, .25" X 1.5", Solid #4, 36 Per Card, White, 25/pkg

### Product Dimensions

Length L (imperial) 1.5 "

Length L (metric) 38.1 mm

Core diameter from / to 3.40 - 7.50 mm

Width W (imperial) 0.25 "

Width W (metric) 6.35 mm

Height H (imperial) 1.5 "

Height H (metric) 38.1 mm

Bundle Diameter min (imperial) 0.13 "

Bundle Diameter min (metric) 3.40 mm

Bundle Diameter max (imperial) 0.29 "

Bundle Diameter max (metric) 7.50 mm

Outside Diameter min. (imperial) 0.13 "

Outside Diameter min. (metric) 3.40 mm

Outside Diameter max. (imperial) 0.29 "

Outside Diameter max. (metric) 7.50 mm

### Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 25

Package Quantity 25

Labels per Column 1

Labels per Row 36  
Labels per Sheet 36

## Material and Specifications

---

**Material** Vinyl Cloth (TYHC)  
**Material Shortcut** TYHC  
**Adhesive** Rubber  
**Shortcut Adhesive** Synthetic rubber  
**Adhesive Operating Temperature** -40 °F to +248 °F (-40 °C to +120 °C)  
**Operating Temperature** -40 °F to +248 °F (-40 °C to +120 °C)  
**ROHS Conformity** Yes