

WC12-1

Article Number: 560-10027

Clip-Tag Marked 1, .177"- .236", Nylon, White, 300/Pkg



Base Data

|                       |  |
|-----------------------|--|
| Local Order Number    | WC12-1   |
| Type                  | WC12   |
| Color                 | White (WH)   |
| Features and Benefits | <ul style="list-style-type: none"><li>• Clip-Tags are snap-on markers which slip easily on wire and cable.</li><li>• Markers are non-adhesive and come on a plastic wand for trouble free installation.</li><li>• Interlocking design of these markers help to keep them aligned and readable.</li><li>• Clip-Tags have an opening on one end which means that they can be used on pre-terminated and pre-installed wires attached to terminal blocks.</li></ul> |
| Color of Print        | Black (BK)   |
| Product Description   | ClipTags are "open" markers that has an open end which can be snapped over pre-terminated cables. Each legend is printed black on white and has a very low profile when applied to wire and cable. Available in printed legends 0 to 9, + and -, each package contains 300 pieces.   |
| Marking Text          | 1  |
| Short Description     | Clip-Tag Marked 1, .177"- .236", Nylon, White, 300/Pkg   |

Product Dimensions

|                                  |               |
|----------------------------------|---------------|
| Length L (imperial)              | 0.139 "       |
| Length L (metric)                | 3.54 mm       |
| Core diameter from / to          | 4.4 - 6.00 mm |
| Outside Diameter min. (imperial) | 0.177 "       |
| Outside Diameter min. (metric)   | 4.4 mm        |
| Outside Diameter max. (imperial) | 0.236 "       |
| Outside Diameter max. (metric)   | 6.00 mm       |

Logistics and Packaging

|                             |      |
|-----------------------------|------|
| Quantity per                | pack |
| Package Quantity (imperial) | 300  |
| Package Quantity            | 300  |
| Carton Quantity             | 300  |

Material and Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Material              | Polyamide 6.6 (PA66)                 |
| Material Shortcut     | PA66                                 |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity       | Yes                                  |

