

WSM60IMHSUVH1



Article Number: 151-00146

Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg



Base Data

Local Order Number WSM60IMHSUVH1

Type WSM60

Color Black (BK)

- Features and Benefits**
- Design makes installation along frame rails fast and easy.
 - Using weld stud eliminates the need for grinding down painted surfaces which saves time.
 - Weld Stud eliminates need for stocking multiple sized metal P-Clamps which saves time and cost.

Product Description When used in conjunction with a cable tie, the Weld Stud Mount eliminates the need for multiple sized p-clamps, nuts, and bolts, and significantly reduce time and labor. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation.

Short Description Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (imperial) 1.3 "

Length L (metric) 33.5 mm

Width W (imperial) 1.0 "

Width W (metric) 27.2 mm

Height H (imperial) 1.0 "

Height H (metric) 27.0 mm

Bundle Diameter max (imperial) 6.0 "

Bundle Diameter max (metric) 152.4 mm

Stud Size (Imperial) 0.24 "

Stud Size (Metric) 6.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40 °F to +230 °F (-40 °C to +110 °C)

ROHS Conformity Yes

